



**Trolleborg.se**  
**Premiär för DMR Dual-band!**  
**Förhandsboka din radio för**  
**leverans i slutet på maj.**  
**2.550kr + frakt**

# MD-2017

## PROFESSIONAL FM TRANSCEIVER



Use Time-Division Multiple-Access (TDMA) digital function

### ENCRYPTION FUNCTION

Dual time slot for repeater  
Dual time slot for point to point

IP67 Waterproof



**Dual-band DMR**

- Transmit interruption
- Group call match (Promiscuous)
- Private call match (Promiscuous)
- GPS Optional
- Dual band,dual wait,dual standby



**Trolleborg.se**



# MD-2017 Use Time-Division Multiple-Access (TDMA) digital function

## Main Functions

- IP67 Waterproof
- GPS Optional
- Use Time-Division Multiple-Access (TDMA) digital function
- Dual time slot for repeater
- Dual time slot for point to point
- Firmware upgradeable
- Lone worker
- Encryption function
- Compatible with Mototrbo Tier I & II
- Single call, group call and all call
- Analog and digital combined
- Remote kill/stun and activate
- Comply with digital protocol ETSI TS 102 361-1,-2,-3
- Color LCD display
- Up to 3000 channels
- Transmit interruption
- Group call match (Promiscuous)
- Private call match (Promiscuous)

## General Transmitter Receiver

General		Transmitter		Receiver	
Frequency	136-174 & 400-480MHz	Power	UHF ≤5W, VHF ≥4W	Analog Sensibility	0.2μV @ 12dB SINAD
Channels	3000	Transmit current	Analog≤1.6A Digital≤0.9A	Digital Sensibility	0.25μV(BER:5%)
Frequency Stability	±1ppm	Standby current	0.18A	Adjacent Channel Selectivity	≤-60dB@12.5KHz
Operating Temperature	-30°C ~ + 60°C	FM Modulation Mode	11K0F3E @ 12.5KHz	Co-Channel Rejection	≥65dB
Operating Voltage	7.4V DC		14K0F3E @ 20KHz	Spurious Response	≥70dB
Dimension (HxWxD)	131.5*36.8*64	4FSKDigital mode	16K0F3E @ 25KHz	Audio Response	+1~-3dB
Weight	300g(with battery)		12.5KHz(data only):	Rated Audio distortion	<5%
Battery Type	Li-ion		7K60FXD	Audio Power	1W
Battery Capacity	2200mAh	modulation distortion	12.5kHz(data and voice):	Modulation Noise	≥45dB@25KHz /≥40dB @12.5KHz
Antenna Impedence	50Ω		7K60FXW		
Audio Output Power	1W @ 16Ω	Hum and Noise	≥45dB@25KHz /≥40dB@12.5KHz		
Channel spacing	12.5KHz	Adjacent Channel Power	≤-60dB@12.5KHz		
		Audio Response	+1~-3dB		
		Digital Protocol	ETSI-TS102 361-1,-2,-3		

### Application scope:

Tourism, entertainment,restaurant, hotel, shopping hall Government, Police, public security

## Standard Accessories



**Trolleborg.se**

Förändringar i specifikationerna kan ske.